

Overwrapper E 3060

Fully automatic machine for the all-round sealing of single or multiple bundles in hot-sealable film.

GMP-compliant and suitable for process integration

The Overwrapper E 3060 in uncompromising pharmaceutical design takes over cartons, places them together or stacks them in bundles and tightly wraps them in film with excess material at either end. The overlapping film at the ends of the bundle is then tightly folded and sealed. All-round sealing offers additional security against counterfeiting because subsequent interference with the product is immediately recognized. Optional integration of a tear-open thread allows clean and easy unpacking of the cartons. Fully wrapped, the bundles are better protected against moisture and splashing.


The maximum infeed capacity of the machine is 500 cartons/minute, resulting in a maximum output of 60 bundles. Optimum guidance and exact dispensing of the film as well as perfect sealing ensure precision and top quality. Operation of the machines is straightforward using the central operating system with 3-D visualization. An Uhlmann packaging line comprising a blister machine, cartoner and end-of-line packaging machine uses the same operating technology throughout.



Overwrapper E 3060

The Overwrapper E 3060 at a glance. Technical data:

Carton size [A x B x H]	max. 130 x 105 x 250 mm	Space required	
Infeed capacity [1/min]	500 cartons	Machine width	approx. 1,400 mm
Bundle size [A x B x H]	max. 250 x 150 x 250 mm	Machine height	approx. 2,000 mm
Output [1/min]	60 bundles	Machine length	approx. 4,300 mm (with standard feeding system)
Film reel diameter	max. 400 mm		



Overwrapper E 3060

Components and features of the Overwrapper E 3060

- Film reels up to 400 mm in diameter
- Film tear control
- Servo-driven precision guidance and exact dispensing of the film
- Perfect sealing mechanism ensures no damage to products
- Heated sealing of the folded film ends with electronic temperature control
- Integration of strict safety and warning functions, e.g. jam control and overload monitoring
- Acrylic glass guards for permanent visual control

Additional advantages of the Overwrapper E 3060

- Fast changeover thanks to few format parts quickly plugged into place without the need for tools and with automatic reference run of all stations at the touch of a button
- GMP-compliant machine design for easy cleaning and maximum pharmaceutical reliability
- Central operating system with 3-D visualization and printer interfaces
- Integration of separate production data acquisition system possible
- Predestined for line integration with the central line control system SCADA
- Low maintenance with lifetime lubrication

Cross sealing station and folding function



Folding and closing station



Germany
Phone +49 (0)7392 702-0
info@uhlmann.de

USA
Phone +1 973 4028855
info@uhlmann-usa.com

Switzerland
Phone +41 (0)61 7022370
info@uhlmann-hoefliger.ch

Great Britain
Phone +44 (0)1252 743-120
info@uhlmann.co.uk

Spain
Phone +34 918 060960
info@uhlmann.es

Sweden
Phone +46 (0)31 450505
info@uhlmann-nordiska.se

Brazil
Phone +55 11 4012 4375
info@uhlmann.com.br

Russia
Phone +7 (495)933 7747
info@pharmaunion.ru

Singapore
Phone +65 673 43150
info@uhlmann-singapore.com

China
Phone +86 21 3302 8658
info@uhlmann.cn

www.uhlmann.de